
This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.


REVISIONS									
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED				
Α		DWG No. WAS 269A9312.	2/19/90	-	-				
2		SCREWS CHANGED FROM AN515-8R5	-	-	-				
3		CHANGED TO ALTERNATE METHOD WITH HOLES FOR STRESS RELIEF.	10/10/2007	WP	G.E.				
4		CH'D ENGRAVE NOTE.	6/9/2009	RJC	-				
4A		CREATED WELDMENT & RENUMBER COMPONENTS.	9/9/2011	SE	RW				
5	15-0296	6 UPDATED TO NEW DRAFTING STANDARDS, -3 ADDED DIM 2X .670 MIN, CH'D DIM WAS 2X .503511 IS 2X .5035083 & -5 CH'D FINISH WAS BLACK OXIDE IS BLACK ZINC ASTM B633 TYPE II SC2.		DPD	JAG				





269A1315 NUT INSTALLATION WRENCH

		DWG NO. 269T9312		REV 5	
		MAT'L	DRAWN BY:	GILBERT	
		UNLESS OTHERWISE SPECIFIE DIMENSIONS ARE IN INCHES	D wed		,
	PG.	.XXX ± .010 FRACTIONS ± 1/8	HEAT TREAT		
		.XX ± .03 ANGLES ±.5°	FINISH		
		1. BREAK ALL SHARP EDGES .015 x 4	5. SPEC		
	2/3	OR .015R 2. DIMENSIONAL LIMITS APPLY AFTE	USED ON MODEL		
	4	PLATING	269		
	1	SCALE 1:2 DATE	1/18/2012	SHEET 1 OF	4

ASSY QTY	ASSY QTY	В/О	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-3	1	WRENCH	4130/4140/4142		2/3
			-5	1	STOP	4130/4140/4142		4
		B/O	-7	3	SCREW	STEEL	8/32 X 5/16 (MCMASTER-CARR #91400A191)	1







(2.310)

